

Technical Data Sheet

Product Description:

Natural Wood Engineered 3-Layer Parquet tiles

Finishing:

Pre-finished

7 Layers of UV cured polyurethane acrylic.

Wood and construction:

3 Layer Parquet with tongue and groove

Top layer


4-5mm Hardwood


Middle Layer

13mm Pine in cross-sectional strips

Bottom Layer

3mm Spruce





Installation:

Decorama engineered parquet tiles are installed on leveled hard screed and fixed via epoxy polyurethane adhesive which is characterized by strong adhesion and flexibility.

Cleaning and Maintenance:

Use a doormat at the front and rear entrance to prevent dirt and grit.

Parquet floor should never be washed or cleaned with wet towels.

Always check air conditioning, central heating, drain connections, and all water piping to avoid water damages.

It is sufficient to use a vacuum cleaner. A slightly dampened cloth can remove dirt and mud. In extreme cases, a few drops of liquid soap can be used.

Decorama For Furniture Manufacturing & Trading 52 Mohamed Farid St. – 11351 Heliopolis – Cairo, Egypt +202 26354485 – 26354134 decorama@decoramaegypt.com www.decoramaegypt.com



QNB AlAhli

BIC: QNBAEGCXXXX Acc No: 20319814478-17 (USD) 20319814480-11 (EUR) 20319814477 (EGP)